



Gasdetektor

Ammoniak

IP65

April.10

Utmärkande Egenskaper

- Kapslingsgrad IP65
- Utgångssignal spänning eller ström
- Spänningsmatning 18-28Vdc
- 4-20mA loop-powered och 3-ledarkoppling 2-10Vdc



Typ	Område Pris	Utsignal	Driftstemperatur	Sek
MSNH3 300VC	30 - 300ppm	4-20mA/2-10Vdc	-15 till +50 C	4000
MENH3 1000VC	0 - 1000ppm	4-20mA/2-10Vdc	-30 till +50C	7000
MPNH3 100VC	0 - 100%UEG	4-20mA/2-10Vdc	-15 till +50C	4000

Alarmenheter

AAW 24	Varningssiren 24Vdc 98-108dB	1000
AAW 230	Varningssiren 230Vac 98-108dB	1500
OA 24	Blixtljus 24Vdc röd	1500
OAW 24	Kombinerad varningssiren och blixtljus 24Vdc 98dB	3000
OAW 230	Kombinerad varningssiren och blixtljus 230Vac 92dB	5000



Varningsskyltar

Gasalarm	Varningsskylt blink "GASALARM" 24Vac/dc	2500
----------	---	------



Tillbehör

Cal 1	Kalibreringskit för CMD	800
Gas	Kalibreringsgas	på begäran
Press	Tryckregulator flödesjusterbar upp till 0,l/min	på begäran
Stain	Rostfri kapsling	1000
Tool	Verktyg för håltagning i rostfri kapsling	1000

